



## Hebei Hailan Bearing Manufacture Co.,...

3.688 Inch | 93.675 Millimeter x 4.594 Inch |  
 116.688 Millimeter x 4.125 Inch | 104.775  
 Millimeter SKF SYR 3.11/16 Pillow Block Bearings



Bearing No. SYR 3.11/16

SYR 3.11/16 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	20.2
EAN	7316577026385
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Concentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1 Inch
Relubricatable	Yes
Insert Part Number	22220
Seals	Trigard
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Double Row   Heavy Duty   Open End   With Set Screw
Long Description	2 Bolt Pillow Block; 3-11/16" Bore; 4-1/8" Base to Center Height; Concentric Collar Mount; Spherical Roller Bearing; 10"



## Hebei Hailan Bearing Manufacture Co.,...

	Minimum Bolt Spacing; 11-3/4" Bolt Spacing Maximum; Relubri
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SYR 3.11/16
Weight / LBS	44.5
B	4.125 Inch   104.775 Millimeter
Nominal Bolt Center to Center	10.9 Inch   276.9 Millimeter
Bolt Spacing Minimum	10 Inch   254Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
d	3.688 Inch   93.675 Millimeter
Bolt Spacing Maximum	11.75 Inch   298.45Millimeter
D	4.594 Inch   116.688 Millimeter
bore diameter:	3.6875 in
bolt center-to-center length:	10-7/8 in
overall length:	14.2500 in
base width:	3-5/16 in
overall height:	8.4375 in
expansion type:	Expansion Bearing (Floating)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
seal type:	Tri-Guard



## Hebei Hailan Bearing Manufacture Co.,...

bore type:	Round
radial dynamic load capacity:	95000 lbf
housing construction:	Solid Pillow Block
radial static load capacity:	110000 lbf
base to bore centerline:	4.2500 in
maximum rpm:	1250 RPM
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYR
locking device:	Concentric Collar
replacement bearing:	22220